

## 磁力鎖



標準型	AR-0090M	AR-0200M	AR-0300M	AR-0600M AR-0600M-DT	AR-0600M-R	AR-1200M-R AR-1200M-DT
外型尺寸(mm)	70(L)X35(W)X20(H)	160(L)X28(W)X17(H)	166(L)X38.5(W)X21(H)	251(L)X47(W)X25(H)	228(L)X38(W)X27(H)	266(L)X73.5(W)X40(H)
吸附鐵板(mm)	62(L)X32(W)X9(H)	130(L)X28(W)X8(H)	130(L)X32(W)X10(H)	185(L)X38(W)X12(H)	185(L)X38(W)X12(H)	185(L)X61(W)X16(H)
拉力(kg)	40	110	150	250	250	500
消耗電流	12VDC-100mA 24VDC-200mA(另購)	12VDC-100mA 24VDC-200mA(另購)	12VDC-370mA 24VDC-185mA(另購)	12VDC-400mA 24VDC-200mA(另購)	12VDC-400mA 24VDC-200mA(另購)	12VDC-500mA 24VDC-250mA(另購)

標準型/開雙門	AR-0600M-DB AR-0600M-DB-DT	AR-1200M-DB AR-1200M-DB-DT	室外型	AR-0400WF(正孔) AR-0400WS(側孔)	AR-1500WF(正孔) AR-1500WS(側孔)	電磁門扣	AR-0180M
外型尺寸(mm)	502(L)X47(W)X25(H)	532(L)X73.5(W)X40(H)	外型尺寸(mm)	164(L)X35(W)X26(H)	203(L)X63(W)X42(H) / 225(L)X65(W)X42(H)	外型尺寸(mm)	100(L)X38(W)X38(H)
吸附鐵板(mm)	185(L)X38(W)X12(H)	185(L)X61(W)X16(H)	吸附鐵板(mm)	130(L)X32(W)X10(H)	185(L)X61(W)X16(H)	吸附鐵板(mm)	75(L)X32(W)X52(H)
拉力(kg)	250	500	拉力(kg)	180	600	拉力(kg)	80
消耗電流	12VDC-400mA 24VDC-200mA	12VDC-500mA 24VDC-250mA	消耗電流	12VDC-370mA 24VDC-185mA	12VDC-500mA 24VDC-250mA	消耗電流	12VDC-200mA 24VDC-100mA

LZ支架	AR-0300MZL	AR-0400MZL	AR-0600MZL	AR-1200MZL	AR-1500MZL-WS	AR-1500MZL-WF
L尺寸(mm)	166(L)X43(W)X33(H)	164(L)X43(W)X33(H)	251(L)X51(W)X33(H)	266(L)X75(W)X48(H)	225(L)X72(W)X48(H)	225(L)X72(W)X48(H)
Z尺寸(mm)	166(L)X50(W)X43(H)	164(L)X50(W)X44(H)	190(L)X50(W)X50(H)	190(L)X72(W)X72(H)	190(L)X72(W)X72(H)	190(L)X72(W)X72(H)

U型玻璃夾	AR-0300(O400)M-U	AR-0600M-U
外型尺寸(mm)	140(L)X43(W)X28(H)	190(L)X43(W)X28(H)

## 陽極鎖



型號	AR-1203A(斷電開門型/通電上鎖)	AR-1203L(斷電開門型/通電上鎖)	AR-1203P(通電開門型/斷電上鎖)
外型尺寸(mm)	200(L)X35(W)X36.5(H)	200(L)X35(W)X36.5(H)	200(L)X35(W)X36.5(H)
吸附鐵板(mm)	102.6(L)X25.4(W)X2(H)	102.6(L)X25.4(W)X2(H)	102.6(L)X25.4(W)X2(H)
電壓	12VDC±0.10% / 24VDC±0.10%	12VDC±0.10% / 24VDC±0.10%	12VDC±0.10% / 24VDC±0.10%
消耗電流	初始1000mA / 待機狀態250mA	初始500mA / 待機狀態130mA	初始1000mA / 待機狀態250mA

支架	AR-1203A-U(U型玻璃夾)	AR-1203A-BR(外掛盒)
外型尺寸(mm)	210(L)X47.3(W)X22(H) / 110(L)X47.3(W)X22(H)	210(L)X44(W)X46(H)

輔助鎖心	AR-1203-KT	AR-1203-KK	AR-1203-KX	AR-1203-TX

型號	LK-1201A	LK-1201B(附燈號顯示)
外型尺寸(mm)	205(L)X32(W)X43(H)	205(L)X32(W)X43(H)
吸附鐵板(mm)	104(L)X32(W)X3.5(H)	104(L)X32(W)X3.5(H)
電壓	12VDC±10%	12VDC±10%
消耗電流	初始900mA / 待機狀態380mA	初始900mA / 待機狀態320mA

支架	LK-1201A-U(U型玻璃夾)	LK-1201A-BR(外掛盒)
外型尺寸(mm)	210(L)X22(W)X50(H) / 110(L)X22(W)X50(H)	210(L)X44(W)X50(H) / 110(L)X44(W)X50(H)

型號(適自動門)	EM-1600-A	AR-1203H-L-12V(斷電開)
外型尺寸(mm)	203(L)X38(W)X41(H)	300(L)X53.5(W)X41(H)
門感角架(mm)		82.5(L)X27(W)X55.5(H)
電壓	12VDC±10%	12VDC±0.10% / 24VDC±0.10%
消耗電流	初始650mA / 待機狀態220mA	初始1000mA / 待機狀態250mA

支架	EM-1600-A-1(夾角)
外型尺寸(mm)	100(L)X38(W)X40(H) / 100(L)X13(W)X40(H)

## 陰極鎖



標準型	AR-YS-130NO	AR-YS-131NO
外型尺寸(mm)	150(L)X39.5(W)X33.5(H)	160(L)X25(W)X30(H)
電壓	12VDC	12VDC
消耗電流	450mA	450mA

## 不鏽鋼按鈕

型號	AR-PB-1A(銀色)	AR-PB-1G(金色)	AR-PB-2A(銀色)	AR-PB-2G(金色)	AR-PB-3A(銀色)
產品照片					
外型尺寸(mm)	115(L)X42(W)X5(H)	115(L)X42(W)X5(H)	115(L)X70(W)X6(H)	115(L)X70(W)X6(H)	115(L)X70(W)X21(H)

## 壓電開關

型號	AR-PB-6A	AR-PB-7A	AR-PB-8A	AR-PB-MDL
雙色LED BR: 藍色&紅色 GR: 綠色&紅色 WR: 白色&紅色				
外型尺寸(mm)	114.3(L)X44.5(W)X7(H)	114.3(L)X69.9(W)X7(H)	86(L)X86(W)X7(H)	212(L)X38(W)X10(H)

## 周邊配備

型號	歐規電源供應器 BP-W12-1000-E0	美規電源供應器 BP-W12-1500-E0	美規電源供應器 BP-W12-1500-US	電源供應器 BP-W15-2400	歐規電源線 CA-AC2-E0	美規電源線 CA-AC2-US
輸入電壓	100-240VAC, 50/60Hz, 0.5A	100-240VAC, 50/60Hz, 0.7A	100-240VAC, 50/60Hz, 0.7A	100-240VAC, 50/60Hz, 0.7A		
輸出電壓	12VDC, 1000mA	12VDC, 1500mA	12VDC, 1500mA	15VDC, 2400mA, 36VA		
外型尺寸(mm)	65(L)X51(W)X66(H)	77(L)X45(W)X26.5(H)	73(L)X51(W)X35(H)	97(L)X46(W)X34(H)	177(線長)	185(線長)

型號	Standard Card(可讀寫厚卡) AR-TAGCT1W50	ISO Card(可讀寫薄卡) AR-TAGC11W50	MIFARE(可讀寫薄卡) AR-TAGC13W50	鑰匙圈(可讀寫) AR-TAGK71W20F	MIFARE鑰匙圈(可讀寫薄卡) AR-TAGK73W20F-MF07
	Standard Card(唯讀厚卡) AR-TAGCT1R50 <th colspan="2">ISO Card(唯讀薄卡) AR-TAGC11R50</th> <th colspan="2">鑰匙圈(可讀寫空白格式) AR-TAGK71W20F-WO</th> <th>MIFARE鑰匙圈(可讀寫薄卡) AR-TAGK73W20F-MF08</th>	ISO Card(唯讀薄卡) AR-TAGC11R50		鑰匙圈(可讀寫空白格式) AR-TAGK71W20F-WO	
型號	鑰匙圈(可讀寫EM格式) AR-TAGK71W20F-EM				
照片	鑰匙圈(唯讀) AR-TAGK71R20F				
資料格式	EM4001/4012	EM4001/4012	MF1	EM4001/4012	MF1
感應頻率	125kHz	125kHz	13.56MHz	125kHz	13.56MHz
通訊方式	非接觸被動式	非接觸被動式	非接觸被動式	非接觸被動式	非接觸被動式
環境溫度	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C
外型尺寸(mm)	54(L)X86(W)X1.8(H)	54(L)X86(W)X0.8(H)	54(L)X86(W)X0.8(H)	47(L)X28(W)X5(H)	47(L)X28(W)X5(H)

  

型號	繼電器模組 AR-821RB	繼電器模組 AR-721RB	繼電器模組 AR-829RB
	照片		
工作電壓	12VDC	12VDC	12VDC
消耗電流	20mA/40mA	40mA	20mA/40mA
輸出接點	1 Form C, 12A at 125VAC, 7A at 250VAC, 7A at 30VDC		
環境溫度	-20°C to +60°C		
外型尺寸(mm)	20(L)X32(W)X29(H)	33.6(L)X47.8(W)X22.6(H)	55(L)X25(W)X17.4(H)